



2 VP 42 EV VACUUM PUMP



Non-contractual photo.

OVERVIEW

2-stage vacuum pump equipped with a vacuum gauge and a solenoid valve. Sturdy and silent, compatible with all CFCs, HFCs and HCFCs, it provides optimum drainage of all refrigerator and air-conditioning refrigeration systems.

TECHNICAL SPECIFICATIONS

- Rapid drainage up to 25 microns
- Vacuum gauge (mbar: 0 to 1000) for monitoring of vacuum level
- Solenoid insulation valve: prevents air return into the refrigeration system once the machine is off or in the event of power failure
- Compact and fitted with a handle for carrying and transporting
- Fin-cooled
- A large filling orifice located on the top of the housing allows for easy oil drainage and filling
- Window for checking oil level
- Charged with ester oil for vacuum pumps
- Anti-vibration base

SPECIFICATIONS

Pump flow rate	42 l/min.
Number of levels	2 levels
Vacuum level	<0.034 mbar (<25 μ)
Input valve with protective cap	1/4" SAE male
Oil volume	200 ml
Power supply	240 V - 50 Hz
Motor	184 W
Net weight	7.2 kg

The information in this article is the result of our studies and of our experience. It is given in good faith but cannot in any way constitute a guarantee from us, or mean that we accept liability, especially in the case of infringement of third parties or of failure by users of our products to abide with the relevant current regulations.

