



VIN-FP-283/002

climalife®

D-TEK SELECT DETECTOR

DESCRIPTION



Non-contractual photo.

D-Tek Select Detector detects all refrigerants including CFCs, HCFCs and HFCs, HFO based blends such as R-448A, R-450A and HFOs like R-1234yf, R-1234ze and R-1233zd. An audible and visual alarm will signal the presence of a leak.

Functional and easy to use, the **D-Tek Select Detector** has an automatic calibration sensor and is supplied in a rigid carry case with replacement filters, rechargeable NiMH battery and adapter.

TECHNICAL FEATURES

- Complies with EN 14624.
- Leak detection by infrared absorption.
- Two sensitivity levels (low - high).
- Visual signal on a scale of 7 LEDs.
- Beep dimmable amplifying is the approach of the leak.
- Calibration and automatic reset with the possibility of selecting a manual mode for resetting.
- Low battery indicator.
- Flexible probe.

SPECIFICATION:

Minimum illumination	3g / year
Supply	Rechargeable NiMH batteries Adaptor
Battery life	≈ 6.5 hours
Infrared cell life	≈ 1000 hours
Probe length	≈ 380 mm
Range of use	-20°C to +50°C
Weight with battery	580g

The information contained in this product sheet is the result of our studies and experience. It is provided in good faith, but should not, under any circumstance, be taken to constitute a guarantee on our part or an assumption of our responsibility. This is particularly the case when third party rights are at stake or in situations where a user of one of our products fails to observe applicable regulations.

For more information visit our website :



http://www.climalife.dehon.com/contact_us