

Leak detection

## GAS DETECTOR

### MGS-410 Stationary leak detector



Non-contractual photo

The **MGS-410** is a refrigerant leak detector for all air conditioning and refrigeration installations.

The device is an independent transmitter-receiver consisting of 1 built-in probe with 1 alarm level which can be used either as a standalone detector or connected to a control system (GTC for example) via a Modbus link.


It can also be connected to an **MGS-402** or **MGS-408** controller to form a true central detection unit with up to 2 detectors for the **MGS-402** and 8 detectors for the **MGS-408**.

The MGS 400 application allows the MGS 410 to be configured, commissioned and maintained using a smartphone. The application can also be used to view measurements in real time, test outputs and calibrate the detector, etc.

It detects HFO / mixtures (HFO-HFC) / HFC HCFC / HC / NH<sub>3</sub> / CO<sub>2</sub>

Fluid	Sensor	Detection range	Operating conditions		
			Temperature	Relative humidity	Pressure
HFO HFO+HFC HFC HCFC	Semiconductor service life 4 to 6 years*	0-1000 ppm	-40°C to +50°C	5 to 90%	0.8 to 1.1 bars
CO <sub>2</sub>	Infra-red service life 5 to 7 years*	0-5000 ppm 0-10 000 ppm 0-20 000 ppm 0-30 000 ppm 0-40 000 ppm 0-50 000 ppm			
R-290 R-600a	Infra-red service life 5 to 7 years*	0-100% LEL			
NH <sub>3</sub>	Electrochemical service life 2 to 3 years*	0-100 ppm 0-300 ppm 0-1,000 ppm 0-5,000ppm	-40°C to +40°C		
			-20°C +40°C		

\*under normal usage conditions



Leak detection

## ALL DETECTORS IN THE MGS 400 SERIES

MGS-410



Non-contractual photo

MGS-450



Non-contractual photo

MGS-460



Non-contractual photo

Properties	MGS-410	MGS-450	MGS-460
Power supply	24 V AC, 4 W maximum		
Visual indicators and alarm status	Tri-colour LED: green, orange, red		
Probe	Fixed, built into the casing	Remote, up to 5m 115 x 136 x 68 mm	
Buzzer	Intensity 72 dB at 10 cm		
Time delay before alarm is triggered after detection	Configurable - 0 to 15 min		
Configurable relays	/	3 relays: high level/low level/fault	
Analogue output	/	1 output 4 to 20 mA	
Modbus RTU digital output	RS-485 terminal Transmission speed in baud: 9600 or 19200, to be configured Data bits: 8 Parity: None, odd or even to be configured Stop bits: 1 or 2, to be configured Repetition duration: 200 ms (minimum)		
Casing	IP66 130 x 130 x 68 mm 260g	IP66 210 x 225 x 85 mm 480g	IP66 165 x 165 x 87 mm 758g
Bluetooth®	Bluetooth® Low Energy, BLE 4.2 for MGS 400 application		

### REGULATORY INFORMATION

European standard NF EN 378-3 dated 1st April 2017 specifies safety requirements for refrigeration systems and heat pumps. When the refrigerant concentration is liable to exceed the practical limit defined in EN 378-1:2016, Appendix C, the detectors must be compliant with the specified requirements and trigger at least one alarm.

**MGS-410** gas detectors meet the requirements of European standard NF EN 378-3: 2017 (section 9 on leak detectors), along with the DEEE (Electrical and electronic equipment wastes) and NF EN 14624 (performance of portable leak detectors and halogenated refrigerant gas detectors).

*The information contained in this product sheet is the result of our studies and of our experience. It is provided in good faith but should not, under any circumstance, be taken to constitute a guarantee on our part or an assumption of our responsibility, especially in the case of infringement of the rights of third parties or where users of our products fail to abide by the relevant current regulations.*



For further information, visit our website:  
[climalife.com/contact\\_us](http://climalife.com/contact_us)



web